

VS-CVI-B2100SP/3

1.3 Megapixel 720P Water-proof IR HDCVI Camera




Model

VS-CVI-B2100SP/3

Features

- 1/3" 1.3Megapixel CMOS
- 25/30/50/60fps@720P
- High speed, long distance real-time transmission
- HD and standard definition switch.
- OSD Menu, control over coaxial cable
- Day/Night(ICR), AWB, AGC, BLC, 3D-DNR,
- 6mm fixed lens (2.8 mm, 3.6mm, 8mm optional)
- Max. IR LEDs length 20m, Smart IR
- IP66, DC12V

Dimensions



Specifications

Model	VS-CVI-B2100SP/3
Camera	
Image Sensor	1/3" 1.3Megapixel CMOS
Effective Pixels	1260(H)×960(V)
Electronic Shutter	4/25s-1/45,000s
Video Frame Rate	1260×720@25 fps ; 1260×720@30 fps ; 1260×720@30 fps ; 1260×720@60 fps
Synchronization	Internal
Min. Illumination	0.01Lux@F1.2(0Lux IR LED on)
Video Output	1-channel BNC HDCVI high definition video output/ CVBS standard definition video output (Can switch)
Camera Features	
Max. IR LEDs Length	20m, Smart IR
Day/Night	Auto(ICR)/B&W/Color
Noise Reduction	2D/3D
OSD Menu	Support
Lens	
Focal length	6mm (2.8 mm, 3.6mm, 8mm optional)
Mount Type	M12
General	
Power Supply	DC12V±10%
Power Consumption	Max 4.2W
Working Environment	-30°C~+60°C/ Less than 95%RH (no condensation)
Transmission Distance	Over 500m via 75-3 coaxial cable
Ingress Protection	IP66
Dimensions(W×D×H)	Φ65mm x154.7mm
Weight	360g
Others	Default: bracket included

sejati4u.com

What Is HD-CVI?

HDCVI vs HD-SDI

Longer Transmission Distance



HDCVI can transmit HD signal up to 300 meters via RG59/ RG6 coaxial Cable

Better Anti-Interference Capability



HDCVI adopts low-frequency modulation technology, making it free from the high-frequency wireless electric radiation to ensure stable video transmission of high image quality